

smartRID SLIK Model No: SPRSL501 | SPRSL504

Wiegand Protocol Card Readers – Smart Card & proximity reader
(Pin optional, BLE also available)



General Description:

smartRID-SLIK comes in compact 125 kHz proximity & 13.56 MHz Mifare® Classic smart card reader that provides security, authentication, and access control to your entryway. This reader utilizes a Wiegand interface to provide a read range up to 3". It is housed in an IP55-rated enclosure for protection from water.

Main Features:

- Distinguishable, Compact, Elegant sleek design for flexible placement
- Available with fully integrated keypad & Bluetooth (*both optional*)
- Ability to read 26 bit card numbers & 32 bit Mifare serial numbers
- Bicolor LED indication
- Pigtail termination

TECHNICAL SPECIFICATIONS

Particulars	smartRID-SLIK	
Model Number	SPRSL501	SPRSL504
Read Range	Up to 8 cms	4-9 cms
Data Read	CSN	CSN/Sector
Type	Proximity Card	Smart Card (Mifare Classic)
Transmit Frequency	125 KHZ	13.56 MHz
Card Read Time	0.1 sec	0.1 sec
Output Interface	Wiegand Format (26 bits)	Wiegand Format (32 bits)
LED Indicator	Bi colour LED	Bi colour LED
Power supply	12 V DC @ 100mA	12 V DC @ 100mA
Dimensions (in mm)	46 L X 21W X 100 H	46 L X 21W X 100 H
Enclosure	ABS Plastic	ABS Plastic
Colour	Black	Black
Cable Specs (Recommended)	5 core, 7/36 shielded cable	5 core, 7/36 shielded cable
Cable Distance (from Controller)	80m (Wiegand)	80m (Wiegand)
Card (Transponder)	NA	Mifare® Series (ISO14443-A)
Keypad	Available	Available
Bluetooth	Available	Available

Note: Product images are for illustrative purposes only and may differ from the actual product. Some products may have an associated image or photo. These are for reference only and should be considered illustrative. Technical Specifications subject to change without any notice.

Smart-I Electronic Systems Pvt Ltd | Bhumi World Industrial Park | Building No D-7 | Unit No 250 to 253 | Pimpas, Bhiwandi | Thane - 421302, Maharashtra.INDIA

Copyright@Smart-I Electronic Systems Pvt. Ltd. All rights reserved. Technical Specifications, Model Number and Product availability subject to change without notice*.

Connect with us Today - www.smartisystems.com or +91-8767-247-247 | +91- 02522-616500

Email: enquiry@smartisystems.com | sales@smartisystems.com